


## 6 x WS (36) + FC 線接觸麻芯

## 6 x WS (31) + FC 線接觸麻芯


Application : Quay Crane, Floating Crane, Gantry Crane

用途 : 碼頭起重機, 船上起重機, 龍門起重機

參考數據 reference information



6 x WS (36) + FC



6 x WS (31) + FC

Dia. 直徑		Minimum Breaking Load in Metric Tons 最低破斷拉力		Approx. Weight 大約重量 Kg/m
(mm)	(inch)	180kg/mm <sup>2</sup> (1770N/mm <sup>2</sup> )	200kg/mm <sup>2</sup> (1960N/mm <sup>2</sup> )	
6.0		2.2	2.4	0.13
8.0	5/16	3.9	4.3	0.24
9.0		4.9	5.4	0.30
10.0		6.0	6.7	0.37
12.0		8.7	9.6	0.54
13.0		10.2	11.3	0.63
14.0		11.8	13.1	0.73
15.0		13.6	15.1	0.84
16.0	5/8	15.4	17.1	0.95
18.0		19.5	21.7	1.21
19.0	3/4	21.8	24.2	1.35
20.0		24.1	26.8	1.49
21.0	13/16	26.6	29.5	1.64
22.0		29.2	32.4	1.80
24.0	15/16	34.7	38.5	2.15
25.0		37.7	41.8	2.33
26.0		40.7	45.2	2.52
28.0		47.3	52.5	2.92
28.6	1-1/8	49.3	54.7	3.05
30.0	1-3/16	54.3	60.2	3.36
32.0		61.7	68.5	3.82
34.0		69.7	77.4	4.31
35.0	1-3/8	73.8	82.0	4.57
36.0		78.1	86.7	4.83
38.0		87.0	96.6	5.38
40.0		96.4	107.1	5.96
42.0		106.3	118.0	6.58
44.0		116.7	129.6	7.22
46.0		127.5	141.6	7.89
48.0		138.9	154.2	8.59
50.0		150.7	167.3	9.32
52.0		163.0	180.9	10.08
54.0		175.8	195.1	10.87
56.0		189.0	209.9	11.69
58.0		202.8	225.1	12.54
60.0		217.0	240.9	13.42
66.0		262.6	--	16.24
68.0		278.7	--	17.24
70.0	2-3/4	295.4	--	18.27
72.0		312.5	--	19.32
74.0		330.1	--	20.41
76.2	3	350.0	--	21.65