



6 x 24 + FC

6 x 24 + FC 線接觸麻芯

Application : Floating Crane, General Engineering

用途 : 船上起重機, 一般建築工程

參考數據 reference information

Dia. 直徑 (mm)	Minimum Breaking Load in Metric Tons 最低破斷拉力			Approx. Weight 大約重量 Kg/m
	150kg/mm ² (1470N/mm ²)	165kg/mm ² (1620N/mm ²)	180kg/mm ² (1770N/mm ²)	
8.0	2.90	3.20	3.50	0.21
9.0	3.70	4.00	4.40	0.26
9.5	4.20	4.50	4.90	0.30
10.0	4.60	5.00	5.40	0.33
11.2	5.80	6.30	6.80	0.41
12.0	6.70	7.20	7.80	0.47
12.6	7.30	7.90	8.60	0.52
13.0	7.80	8.40	9.20	0.56
14.0	9.10	9.80	10.70	0.65
14.3	9.50	10.30	11.20	0.67
15.0	10.50	11.30	12.30	0.74
16.0	11.90	12.80	14.00	0.85
17.5	14.20	15.40	16.80	1.01
18.0	15.10	16.30	17.70	1.07
19.0	16.80	18.10	19.80	1.19
20.0	18.60	20.10	21.90	1.32
21.0	20.50	22.10	24.10	1.46
22.4	23.30	25.20	27.50	1.66
24.0	26.80	28.90	31.50	1.91
25.0	29.10	31.40	34.20	2.07
25.4	30.00	32.40	35.30	2.14
26.0	31.40	33.90	37.00	2.24
28.0	36.50	39.30	42.90	2.60
28.6	38.00	41.00	44.80	2.71
30.0	41.90	45.20	49.30	2.98
32.0	47.60	51.40	56.10	3.40
34.0	53.80	58.00	63.30	3.83
35.0	57.00	61.50	67.10	4.06
36.0	60.30	65.00	71.00	4.30
38.0	67.20	72.50	79.10	4.79
40.0	74.40	80.30	87.60	5.31
41.5	80.10	86.40	94.30	5.71
42.0	82.00	88.50	96.60	5.85
44.0	90.00	97.20	106.00	6.42
44.5	92.10	99.40	108.00	6.57
46.0	98.40	106.00	116.00	7.02
48.0	107.00	116.00	126.00	7.64
50.0	116.00	125.00	137.00	8.30
50.8	120.00	130.00	141.00	8.56
52.0	126.00	136.00	148.00	8.97
54.0	136.00	146.00	160.00	9.68
56.0	146.00	157.00	172.00	10.41
57.2	152.00	164.00	179.00	10.86
58.0	156.00	169.00	184.00	11.17
60.0	167.00	181.00	197.00	11.95