

6 x WS (36) + IWRC


6 x WS (36) + IWRC

Conventional Plastic Injected 注塑線接觸鋼芯

Application : Special Crane, Floating Crane, Gantry Crane

用途 : 碼頭起重機, 船上起重機, 龍門起重機

参考数据 reference information



Dia. 直徑		Minimum Breaking Load in Metric Tons 最低破斷拉力			Approx. Weight 大約重量 Kg/m
(mm)	(inch)	180kg/mm ² (1770N/mm ²)	200kg/mm ² (1960N/mm ²)	220kg/mm ² (2160N/mm ²)	
22.0		34.00	36.90	40.00	2.18
22.2	7/8	34.70	37.60	40.80	2.22
24.0	15/16	40.40	43.90	47.60	2.59
25.0		43.90	47.60	51.60	2.81
25.4	1	45.30	49.10	53.30	2.90
26.0		47.40	51.50	55.80	3.04
28.0		55.00	59.70	64.70	3.53
28.6	1-1/8	57.40	62.30	67.50	3.68
30.0	1-3/16	63.20	68.60	74.30	4.05
31.8	1-1/4	71.00	77.00	83.50	4.55
32.0		71.90	78.00	84.60	4.61
34.0		81.10	88.10	95.50	5.20
35.0	1-3/8	86.00	93.30	101.2	5.51
36.0		91.00	98.70	107.0	5.83
38.0		101.3	110.0	119.2	6.50
38.1	1-1/2	101.9	110.6	119.9	6.53
40.0		112.3	121.9	132.1	7.20
42.0		123.8	134.4	--	7.94
44.0		135.9	147.5	--	8.71
44.5	1-3/4	138.7	150.5	--	8.89
46.0		148.5	161.2	--	9.52
48.0		161.7	175.5	--	10.36
50.0		175.4	190.5	--	11.25
50.8	2	181.1	196.6	--	11.61
52.0		189.8	206.0	--	12.16
54.0		204.6	222.1	--	13.12
56.0		220.1	238.9	--	14.11
57.2	2-1/4	229.6	249.3	--	14.72
58.0		236.1	256.3	--	15.13
60.0		252.6	274.3	--	16.20
63.5	2-1/2	283.0	307.2	--	18.14
66.0		305.7	--	--	19.60
68.0		324.5	--	--	20.80
70.0	2-3/4	343.9	--	--	22.04
72.0		363.8	--	--	23.32
74.0		384.3	--	--	24.63
76.2	3	407.5	--	--	26.12